

Pyrogel ® 2250, 3250, 6250, 9250

Revision Date: 4/10/08

1. IDENTIFICATION OF THE SUBSTANCE AND OF THE COMPANY

Product Name: Pyrogel® 2250, 3250, 6250, 9250

Synonyms: Silica gel, trimethylsilylated; silica aerogel materials

Use of the Substance/Preparation: High performance insulation material

Manufacturer: Aspen Aerogels, Inc. Address: 30 Forbes Road

Northborough, MA 01532

Telephone: (508) 691-1111

Emergency Telephone Number: 800-535-5053 US (INFOTRAC) 352-323-3500 International

2.HAZARDS IDENTIFICATION

Appearance and Odor:

Black fabric material with no characteristic odor. Under certain conditions, product may have

faint ammonia-like odor.

Emergency Overview:

Inhalation of excessive amounts of dust from the product may cause mechanical irritation to the

respiratory tract. Dermal contact may cause mechanical irritation.

POTENTIAL HEALTH EFFECTS

Inhalation: Inhalation of airborne dusts may cause mechanical irritation of the upper respiratory tract.

Eye Contact: Exposure to dust from this product can produce a drying sensation and mechanical irritation of

the eyes.

Skin Contact: Skin contact with dust from this product can produce a drying sensation and mechanical

irritation of the skin and mucous membranes.

Ingestion: This material is not intended to be ingested (eaten). If ingested in large quantity, the material

may produce mechanical irritation and blockage

Acute Health

Hazards:

Dust from this product is a physical irritant, and may cause temporary irritation or scratchiness

of the throat and / or itching and redness of the eyes and skin.

Chronic Health Hazards:

Some studies of long term amorphous silica dust exposures indicate a potential for decreased lung function. In surveyed studies, this effect is characterized as compounded by smoking. Additionally, surveyed studies characterize the decreased lung function effect as reversible on

discontinuation of exposure.

This product contains a proprietary opacifier whose elemental components include copper and manganese. Because of the structure of the copper and manganese and the respective weight percentage in this proprietary component, exposure to these elements is expected to be below levels which would cause chronic health effects. The final product contains less than 1% of each of these elements. Chronic overexposure to manganese and its compounds may have

effects on the lungs and central nervous system.

Medical Conditions Aggravated by

Exposure:

Excessive inhalation of dust may aggravate pre-existing chronic lung conditions including, but not limited to, bronchitis, emphysema, and asthma. Dermal contact may aggravate existing

dermatitis.

CARCINOGENICITY

Component	ACGIH	NTP	IARC
Amorphous Silica	NA	Not Listed	3
Oxidized polyacrylonitrile fiber	NA	Not Listed	None
Proprietary opacifier	A4	Not Listed	None



Pyrogel ® 2250, 3250, 6250, 9250

Revision Date: 4/10/08

SECTION 2 NOTES: This product is composed of synthetic amorphous silica dioxide, often referred to as silica gel or amorphous precipitated silica. Amorphous silica should not to be confused with crystalline silica. Epidemiological studies indicate low potential for adverse health effects from exposure to amorphous silica. The ACGIH A4 designation is based on the base ingredients in the proprietary opacifier.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	Percent	CAS Number	EINECS Number	EU Classification
Silica gel, trimethylsilylated	50-70	126877-03-0	Not Assigned	None
Oxidized polyacrylonitrile fiber	30-50	NA	Not Assigned	None
Proprietary Opacifier ^a	NA	0-2	NA	None

^a Product contains a proprietary opacifier whose elemental components include copper and manganese. The final product contains less than 1% of each of these elements.

4. FIRST AID MEASURES

Eye Contact: Immediately wash with large amounts of water for at least 15 minutes, occasionally lifting lids.

If irritation occurs and persists, get medical treatment.

Skin Contact: Wash skin thoroughly with soap and plenty of water. Remove contaminated clothing and shoes.

Wash clothing before reuse. Obtain medical attention if symptoms occur.

Ingestion: Material will pass through the body normally.

Inhalation: Remove to fresh air. Drink water to clear throat and blow nose to remove dust. Obtain medical

attention if ill effects persist.

5. FIRE-FIGHTING MEASURES

5.1 FLAMMABILITY PROPERTIES

Auto ignition Temperature	Not Applicable
Flash Point	Not Applicable
Flammability Limits: (Lower Explosive Limit)	Not Applicable
Flammability Limits: (Upper Explosive Limit)	Not Applicable

5.2 EXTINGUISHING MEDIA:

Use media suitable for surrounding fire and that are appropriate to the surrounding environment; normal fog nozzle water application and/or exclusion of air is typically suitable for extinguishing this product in blanket form.

5.3 PROTECTION FOR FIRE FIGHTERS

Special Fire Fighting Procedures:

Normal fire fighting procedures should be followed to avoid inhalation of smoke and gases produced by a fire.

Unusual Fire and Explosion Hazards:

Product is a super-insulation material. Rolls of material can retain heat within internal layers causing re-ignition in the presence of oxygen if heat is not removed.

Hazardous Decomposition Products:

Primary combustion products are carbon monoxide and carbon dioxide. The product contains polyacrylonitrile. If involved in combustion events, product can evolve trace amounts of; NH3 (ammonia), HCN (hydrogen cyanide), and monomeric

acrylonitrile.



Pyrogel ® 2250, 3250, 6250, 9250

Revision Date: 4/10/08

6. ACCIDENTAL RELEASE MEASURES

Personal Precautions: Minimize dust generation. Ensure adequate ventilation. Use personal protective

equipment as necessary.

Environmental Precautions: Material is not soluble. Do not flush into surface water or sanitary sewer system.

Methods for Cleaning Up: Contain and collect released material for proper disposal. Dry vacuuming is the

preferred method of cleaning up dust.

7. HANDLING AND STORAGE

Aerogel blankets will generate dust when handled. Workplace exposure to all dusts should be Handling

> controlled with standard industrial hygiene practices. Local exhaust ventilation should be the primary dust control method. Dust released during the handling of aerogel blankets should be cleaned up promptly. Dry vacuuming is the preferred method for cleaning up dust. Sweeping is not an effective method of picking up aerogel dust. Because aerogel dust is hydrophobic, water is not effective as a dust

control agent.

Aerogel blankets should be kept in their packaging until they are ready to be used. Unpack the material Storage

in the work area. This will help to minimize the area where dust exposure may occur. Trimmed

material and scrap should be promptly packed in disposal bags.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Exposure Limit Values

There are no exposure limits identified for the main product component, classified as synthetic amorphous silica. Exposure limits for synthetic amorphous silica are based on silica (CAS No. 7631-86-9).

CAS Number	Component Name	Exposure Limits
------------	----------------	-----------------

7631-86-9 Germany TRGS 900 4 mg/m³ (inhalable fraction) Silica, Amorphous

6 mg/m³ (total inhalable fraction) UK WEL 2.4 mg/m³ (respirable fraction)

US OSHA PEL (TWA)^a: 15 mg/m³ (total dust)

5 mg/m³ (respirable fraction)

US ACGIH^b 10 mg/m³ (inhalable)

3 mg/m³ (respirable)

NA Proprietary opacifier^c NA

8.2 Exposure Control

Local exhaust in accordance with general industrial hygiene practices is recommended to Ventilation:

control dust.

A properly fitted, NIOSH or CE approved respirator should be worn when ventilation is **Respiratory Protection:**

> unavailable or inadequate to maintain airborne concentrations below applicable occupational exposure limits. A respiratory protection program that meets applicable local regulations should be implemented whenever workplace conditions warrant use of

a respirator.

^a The US OSHA standard for amorphous silica is: (80 mg/m³)/(%SiO2). The NIOSH Sampling Method 7501 for Amorphous Silica calculates the %SiO2 based on the percentage of crystalline silica in the sample. Because the percentage of crystalline silica in aerogel is 0%, the particulate limit applies.

^b US ACGIH based on Particles Not Otherwise Specified (PNOS)

^c Product contains a proprietary opacifier whose elemental components include copper and manganese. The final product contains less than 1% of each of these elements. According to the manufacturer of the opacifier, there is no specific exposure limit for this material. Based on the percentage of these elements in the final product, the applicable amorphous silica exposure limit would be exceeded before the copper compounds and manganese compounds exposure limits would be exceeded.



Pyrogel ® 2250, 3250, 6250, 9250

Revision Date: 4/10/08

Hand Protection Silica aerogels are hydrophobic (repel water) and may cause drying and irritation of the

skin, eyes, and mucous membranes. For this reason, nitrile, latex, or other impermeable

gloves should be worn when handling aerogel blankets.

Eye Protection: Safety glasses, or chemical goggles as needed to provide greater protection from dust.

Skin Protection: Long-sleeved, long-legged work clothes are also advised. Disposable coveralls should

be considered to minimize skin exposure and track out of aerogel dusts into adjacent

areas.

Work Hygienic

Practices

Keep materials packaged until just prior to use. Die cut in preference to rotary or other cutting methods. Dry vacuum with proper filtration preferred to sweeping. Wash

thoroughly after using the product. Wash clothing if dusty conditions present. Wash

hands before eating or drinking.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: Black fabric blanket

Odor: No characteristic odor. Under certain conditions, product may have faint ammonia-like odor.

pH: Not applicable. **Boling Point/Range:** Not applicable. **Flash Point:** Not applicable. Flammability (solid, gas): Not applicable. Not applicable. **Explosive Properties: Oxidizing Properties:** Not applicable. **Vapor Pressure:** Not applicable. Insoluble. **Solubility:** Viscosity: Not applicable. **Evaporation Rate:** Not applicable

10. STABILITY AND REACTIVITY

Chemical Stability: Stable

Conditions to Avoid: Prolonged exposure to temperatures above the recommended use temperature.

Materials to Avoid: None Known.

Hazardous Please refer to Section 5.3 for products of combustion. Under recommended usage

Decomposition Products conditions, hazardous decomposition products are not expected.

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

Dust may cause mechanical irritation and dryness to eyes and skin.

Synthetic Amorphous Silica

 Oral LD50:
 >5,000 mg/kg

 Inhalation LC50:
 >2,000 mg/m³

 Dermal LD50:
 >3,000 mg/kg

Eye Irritation: Synthetic amorphous silica and silicates are not irritating to skin and eyes under

experimental conditions, but may produce dryness following prolonged and repeated

exposure.

Skin Irritation: Synthetic amorphous silica and silicates are not irritating to skin and eyes under

experimental conditions, but may produce dryness following prolonged and repeated exposure. This material was determined to be non-irritating by the MatTek Epiderm

MTT Viability Assay.



Pyrogel ® 2250, 3250, 6250, 9250

Revision Date: 4/10/08

CHRONIC TOXICITY

Some studies of long term amorphous silica dust exposures indicate a potential for decreased lung function. In surveyed studies, this effect is characterized as compounded by smoking. Additionally, surveyed studies characterize the decreased lung function effect as reversible on discontinuation of exposure.

CARCINOGENICITY

The International Agency for Research on Cancer (IARC) considers synthetic amorphous silica to be not classifiable as to its carcinogenicity to humans (Group 3). The elements in the proprietary opacifier are considered A4 (Not Classifiable as a Human Carcinogen) by ACGIH.

NOTE TO SECTION 11: Toxicological information is based on literature review for synthetic amorphous silica (CAS No. 7631-86-9)

12. ECOLOGICAL INFORMATION

Aquatic Toxicity

Synthetic Amorphous Silica Fish: LC50 > 10,000 mg/L (Brachydanio rerio: 96 hour), Method OECD 203

Daphnia magna: EC50 > 10,000 mg/l (24 hours), Method OECD 202

Mobility None expected due to insoluble nature of product.

Persistence and Biodegradability Not applicable for inorganic material.

Bioaccumulative PotentialNone expected due to insoluble nature of product.

Other Adverse Effects None expected.

NOTE TO SECTION 12: Ecological information is based on literature review for synthetic amorphous silica (CAS No. 7631-86-9)

13. DISPOSAL CONSIDERATIONS

Dispose in an approved landfill in accordance with federal, state / provincial, and local regulation. Cover promptly to avoid dust generation. This product is not regulated as a hazardous waste under US RCRA regulations.

14. TRANSPORT INFORMATION

Shipping Name: Not regulated for transport

Hazard Class None
UN Number None
Packing Group None
Required Label(s) None
Marine Pollutant No
Additional Information None

15. REGULATORY INFORMATION

EC REGULATORY INFORMATION

Product is not a classified as a dangerous material or preparation as defined in EC Directives 67/548/EEC or 1999/45/EC.

U.S. FEDERAL REGULATIONS

CERCLA (Comprehensive Response Compensation and Liability Act): Product is not classified as hazardous or reportable under this requirement.

SARA TITLE III (Superfund Amendments and Reauthorization Act): Product is not classified as hazardous or reportable under this requirement.



Pyrogel ® 2250, 3250, 6250, 9250

Revision Date: 4/10/08

311/312 HAZARD CATEGORIES: Materials in this product are classified as hazardous or reportable under this requirement.

313 REPORTABLE INGREDIENTS: Materials in this product are classified as hazardous or reportable under this requirement.

STATE REGULATIONS: Materials in this product appear on the following state hazardous substance lists: CA, IN, KY, MA, MN, NC, NJ, OR, PA. Check individual state requirements

INTERNATIONAL REGULATIONS Amorphous silica (CAS No. 7631-86-9) is listed on the WHMIS Ingredient Disclosure List at a concentration threshold of 1 %.

TSCA: All chemical substances in this material are included on or exempted from listing on the TSCA Inventory of Chemical Substances."

16. OTHER INFORMATION

NFPA HAZARD CLASSIFICATION HMIS HAZARD CLASSIFICATION

Health1Health1Flammability1Flammability1Reactivity0Reactivity0

Other N/A Protection Please refer to Section 8.

ABBREVIATIONS:

NA: Denotes no applicable information found or available.

CAS Number Chemical Abstract Service Number

EINECS Number
ACGIH
European INventory of Existing Chemical Substances
American Conference of Governmental Industrial Hygienists
US OSHA
United States Occupational Safety and Health Administration

TLV Threshold Limit Value
PEL Permissible Exposure Limit
TWA Time-weighted average

IARC International Agency for Research on Cancer

EC European Commission
NTP National Toxicology Program

R Risk Safety

LC50 Lethal Concentration 50%

LD50 Lethal Dose 50%

NFPA National Fire Protection Association
HMIS Hazardous Materials Identification System
US DOT United States Department of Transportation
TDG Transportation of Dangerous Goods Regulation

Section 11 Synthetic Amorphous Silica Toxicity Information Reference: United Nations Environmental Programme (UNEP), Organization for Economic Co-operation and Development (OECD) Screening Information Data Set (SIDS) Initial Assessment Report, Synthetic Amorphous Silica, July 23, 2004.

Revision Summary: This revised safety data sheet replaces all previous versions. The safety data sheet was modified for product formulation change.

DISCLAIMER: The information herein is presented in good faith and believed to be accurate as of the effective data given. However, no warranty, expressed or implied, is given. It is the user's responsibility to ensure that its activities comply with Federal, State or Provincial, and local laws.